

RTV

RTV1140

SPECIFICATIONS

Specifications

| Model | | RTV1140CPX Orange | RTV1140CPX RealTree® Camouflage |
|---------------------------------------|----------------------------------|--|---|
| Engine | Make | KUBOTA D1105-E3-UV | |
| | Type | 3-cylinders, Water cooled 4-cycle, diesel, OHV | |
| | Displacement | cu.in (cc) | 68.5 (1123) |
| | Horsepower | HP (kW)/rpm | 24.8 (18.5)@3000 |
| Fuel tank capacity | U.S.gals (ℓ) | 7.9 (30) | |
| Transmission | | Variable hydro transmission (VHT Plus) | |
| Max. Traveling speed | mph (km/h) | 25 (40) | |
| Wheels, drive system | | 4, Rear 2WD or 4WD | |
| Differential lock | | Standard; foot operated with mechanical holder | |
| Gear selection | | Hi-Med-Lo range forward, neutral, reverse | |
| Brakes | Front / Rear | Wet-disc brake | |
| | Parking brake | Rear wheel, hand lever | |
| Steering | | Hydrostatic power | |
| Suspension | Front / Rear | Independent, Mac-Pherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorbers | |
| Dimensions | Length | in. (mm) | 137.0 (3480) |
| | Width | in. (mm) | 61.0 (1550) |
| | Height, overall | in. (mm) | 78.7 (2000) |
| | Front tread centers | in. (mm) | 45.3(1150) w/HDWS & ATV, 46.5 (1180) w/Turf |
| | Rear tread centers | in. (mm) | 46.5(1180) w/HDWS & ATV, 47.6 (1210) w/Turf |
| | Wheelbase | in. (mm) | 95.1 (2415) |
| | Ground clearance front/rear axle | in. (mm) | 8.3 (210) / 7.5 (190) |
| | Turning diameter | ft. (m) | 32.8 (10) |
| Max. rolling weight (Towing capacity) | lbs. (kg) | 1300 (590) | |
| Payload capacity | lbs. (kg) | 1609 (730) | |
| Weight | lbs. (kg) | 2370 (1075) | |
| Cargo bed | Width × Length × Depth | in. (mm) | 1ROW:52.0(1320)×53.5(1360)×11.4(290) 2ROWS:52.0(1320)×33.9(860)×11.4(290) |
| | Volume | cu ft. (m ³) | 1ROW:18.7(0.53) 2ROWS:11.7(0.33) |
| | Bed height (unloaded) | in. (mm) | 33.5 (850) |
| | Cargo bed load | lbs. (kg) | 1ROW:1102(500) 2ROWS:661(300) |
| Tires | Front | 25×10-12 HDWS, 6PLY | 25×10-12 HDWS, 6PLY |
| | | 25×10-12 ATV, 6PLY | 25×10-12 ATV, 6PLY |
| | | 25×12-12 Turf, 4PLY | — |
| | Rear | 25×10-12 HDWS, 6PLY | 25×10-12 HDWS, 6PLY |
| | | 25×11-12 ATV, 6PLY | 25×11-12 ATV, 6PLY |
| | | 25×12-12 Turf, 4PLY | — |
| Front guard | | Std. | |
| Hydraulic bed lift | | Std. | |
| Speedometer | | Std. | |

**RealTree® is a registered trademark of Jordan Outdoor Enterprises, Ltd.
The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information.
The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires. Some RTVs in this web site are shown with optional accessories. For off-highway use only.