

RTV-X Series

Specifications

RTV-X1100C



Model			RTV-X1100C	
Body color			Kubota Orange	Realtree AP Camo
Engine	Make		KUBOTA D1105-E4-UV	KUBOTA D1105-E4-UV
	Type		3-cylinders, 4-cycle, diesel, OHV	3-cylinders, 4-cycle, diesel, OHV
	Displacement	cu.in (cc)	68.5 (1123)	68.5 (1123)
	Horsepower	HP (kW)/rpm	24.8 (18.5) @3000	24.8 (18.5) @3000
	Cooling system		Liquid	Liquid
	Battery		650 CCA	650 CCA
Transmission			Variable hydro transmission (VHT-X)	Variable hydro transmission (VHT-X)
Gear selection			Hi-Lo range forward, neutral, reverse	Hi-Lo range forward, neutral, reverse
Max. traveling speed			0-25 (0-40) mph (km/h)	0-25 (0-40)
4WD system	Front differential		Limited-slip differential	Limited-slip differential
	Rear differential		Foot operated differential lock	Foot operated differential lock
Steering			Hydrostatic power	Hydrostatic power
Brakes	Front / Rear		Wet-disc brakes	Wet-disc brakes
	Parking brake		Rear wheel, hand operated	Rear wheel, hand operated
Suspension	Front suspension		Independent, Dual A-arms with adjustable spring preload	Independent, Dual A-arms with adjustable spring preload
	Front suspension travel	in. (mm)	8 (205)	8 (205)
	Rear suspension		Independent with coil over shock	Independent with coil over shock
	Rear suspension travel	in. (mm)	8 (205)	8 (205)
Headlights			Two 37.5 watt halogen	Two 37.5 watt halogen
Occupant Protective System (OPS)	Tubular overhead structure	in. (mm)	2.0 (50.8) steel tube	2.0 (50.8) steel tube
	Seat belts		2-point	2-point
	Certification		SAE J2194 and OSHA 1928 ROPS	SAE J2194 and OSHA 1928 ROPS
Dimensions	Length	in. (mm)	122.5 (3110)	122.5 (3110)
	Width	in. (mm)	65.4 (1660)	65.4 (1660)
	Height, overall	in. (mm)	82.3 (2090)	82.3 (2090)
	Front tread centers	in. (mm)	48.8 (1240)	48.8 (1240)
	Rear tread centers	in. (mm)	48.8 (1240)	48.8 (1240)
	Wheelbase	in. (mm)	80.5 (2045)	80.5 (2045)
	Turning radius	ft. (m)	13.1 (4.0)	13.1 (4.0)
Weight		lbs. (kg)	2370 (1075)	2370 (1075)
Towing capacity		lbs. (kg)	1300 (590)	1300 (590)
Payload capacity		lbs. (kg)	1629 (739)	1629 (739)
Ground clearance	Front	in. (mm)	10.5 (266)	10.5 (266)
	Rear	in. (mm)	10.4 (263)	10.4 (263)
	Under foot platform	in. (mm)	11.0 (280)	11.0 (280)
Cargo bed	Material		Steel	Steel
	Width x Length x Depth	in. (mm)	57.7 (1465) x 40.5 (1030) x 11.2 (285)	57.7 (1465) x 40.5 (1030) x 11.2 (285)
	Volume	cu ft. (m3)	15.2 (0.43)	15.2 (0.43)
	Bed height (unloaded)	in. (mm)	34.9 (887)	34.9 (887)
	Cargo bed load	lbs. (kg)	1102 (500)	1102 (500)
	Dump		Hydro power lift	Hydro power lift
Fuel tank capacity		U.S. gals (L)	7.9 (30)	7.9 (30)
Sound rating at operator's ear		dB. (A)	83	83
Tires	Front and Rear	ATV	25x10-12, 6PLY	25x10-12, 6PLY
		HDWS	25x10-12, 6PLY	25x10-12, 6PLY
		TURF	25x10-12, 4PLY	—
Front guard design			Center, bumper and lens	Center, bumper and lens
Alloy wheel (not available with Turf tire)			Opt.	Opt.
Hydraulic bed lift			Std.	Std.
Spray-on Bed Liner			Opt.	Opt.

*New SAE J1940

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warrant. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.