

SVL

SVL75-2

SPECIFICATIONS

Specifications

Model		SVL75-2		
Type of operator station		Open CAB / Closed CAB		
Engine	Model	V3307-CR-TE4		
	Gross HP	HP (kW)/rpm	74.3 (55.4)/ 2400	
	Displacement	cu.in. (cc)	203.3 (3331)	
	Cylinders		4	
	Bore × stroke	in.(mm)	3.7 (94) × 4.72 (120)	
	Aspiration		Turbocharged	
Loader performance	Rated operating capacity-35% tipping load	lbf. (kg)	2300 (1043)	
	Rated operating capacity-50% tipping load	lbf. (kg)	3285 (1490)	
	Tipping load	lbs. (kg)	6570 (2980)	
	Breakout force	Bucket	lbf. (kg)	6204 (2814)
		Lift arm	lbf. (kg)	4766 (2162)
	Lifting capacity	lbs. (kg)	4881 (2214)	
Lift arm path		Vertical		
Undercarriage	Track width	Standard	in. (mm)	12.6 (320)
		Wide	in. (mm)	15.0 (380)
	Ground pressure with standard track	psi	5.6 / 5.8	
	Ground pressure with wide track	psi	4.7 / 4.9	
	Track rollers (per side)		4	
	Track ground contact length	in. (mm)	56.5 (1436)	
	Travel speed	Low	mph (km/h)	4.7 (7.5)
		High	mph (km/h)	7.1 (11.5)
Traction force	lbf. (kg)	9678 (4390)		
Min. ground clearance	in. (mm)	11.7 (296)		
Hydraulic system	Aux. hydraulic flow	gpm (ℓ/min.)	17.4 (66.0)	
	Aux. hydraulic pressure	psi (kgf/cm ²)	3185 (224.0)	
	Hydraulic system	gal. (ℓ)	15.9 (60)	
Service refill capacities	Hydraulic tank	gal. (ℓ)	9.2 (35)	
	Fuel tank	gal. (ℓ)	24.6 (93)	
Operating weight (include operator weight 175lbs.)		lbs. (kg)	8984 (4075) / 9260 (4200)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

SVL

SVL75-2

SPECIFICATIONS

Dimensions

Model			SVL75-2
A	Length of track on ground	in. (mm)	56.9 (1446)
B	Track gauge	in. (mm)	53.3" (1355)
C	Length w/o bucket	in. (mm)	109" (2768)
D	Length w/bucket on ground	in. (mm)	138.9" (3527)
E	Height to top of cab	in. (mm)	82" (2083)
F	Bucket pin height at max. lift	in. (mm)	119.2" (3027)
G	Rollback angle at carry position	degree	27
H	Reach at max. lift and dump	in. (mm)	40.9" (1038)
I	Ground clearance	in. (mm)	11.7" (296)
J	Departure angle	degree	31.5
K	Max. dump angle	degree	41.5
L	Vehicle width	in. (mm)	65.9" (1675)
M	Width with bucket	in. (mm)	68" (1727)
N	Turning radius from center-machine rear	in. (mm)	107.1" (2720)

