

T H E S U L L A I R

375


PORTABLE AIR COMPRESSOR

375 CFM AT 100 PSIG—177 L/S AT 7 BAR



- ROTARY SCREW COMPRESSOR
- REMOVABLE MODULAR CANOPY
- ADJUSTABLE HEIGHT HITCH
- E-Z LUBE AXLE
- LARGE TOOL BOX COMPARTMENT
- CURBSIDE INSTRUMENT PANEL
- SSAM—SHUTDOWN SYSTEM & ANNUNCIATION MODULE
- PROTECTIVE SHUTDOWN SWITCHES
- IDLE WARM-UP VALVE
- ROCKER TYPE START SWITCH
- FUEL/WATER SEPARATOR
- TWO STAGE AIR FILTERS
- 0 TO 100% CAPACITY CONTROL
- PNEUMATIC INLET VALVE
- AWF COMPRESSOR FLUID
- DURABLE POWDER COAT FINISH
- WIDE TRACK
- BUMPER WITH RECESSED TAIL LIGHTS





Large Tool Box Compartment
Sullair pneumatic tool sold separately.



E-Z Lube Axle
Offers convenient wheel bearing lubrication thru zerk fittings.



Rotary Screw Compressor
Single-stage, fluid flooded. Cast iron housing is dimensionally stable, thick-walled and machined to close tolerances.



Rear Bumper
Features recessed tail lights and license plate light.

DESIGNED FOR TOTAL ACCESSIBILITY AND RELIABILITY

Rotary Screw Compressor

Ample Service Doors

Large side doors provide access to fuel tank, engine, compressor and tool compartment.

Rear service panel provide access to side-by-side compressor fluid cooler and engine radiator.

Serviceable components within easy reach. Routine maintenance is simplified.

Reduced downtime and service cost.

Service doors feature non-rusting hinges and stainless steel T-type door retainers.

Multi-Piece Canopy

Easy and inexpensive to replace, if damaged.

Easily removed as one assembly for major service.

Exposed, single point lifting bail.

0 to 100% Capacity Control

Pneumatic inlet valve and unloaded starting.

Highway Towable Running Gear

3" square drawbar.

Adjustable height hitch (15", 17", 19").

Quick-change hitch.

Screw jack with pad.

Transport security chains.

E-Z lube axle lubrication.

Heavy duty leaf spring suspension.

Curbside Instrument Panel

Hinged, padlockable cover.

Mechanical air pressure gauge and

hourmeter.

Rocker type engine start switch.

Idle warm-up valve.

SSAM—Shutdown System & Annunciation Module*

Shutdown with annunciator light for high compressor temperature, high engine coolant temperature, low engine oil pressure and engine underspeed.

Engine warning and shutdown fault code annunciation.**

Electronic engine speed control.**

*Patent Pending **John Deere only

Two-Stage Dry Type Air Filters

Separate filters for engine and compressor.

Durable, Baked-On Powder Coat Finish

AWF Compressor Fluid

All-weather, all-climate fluid.

Air End Warranty

2 year standard warranty.

5 year or 10,000 hour warranty when continuously serviced at the recommended intervals with Sullair AWF Compressor Fluid and filters.

Quiet Operation

Meets US EPA Sound requirements of 76 dBA @ 7 meters.



This product is manufactured to the highest quality standards in an ISO 9001 certified quality system.

SULLAIR'S OPTIONS ALLOW YOU TO CUSTOMIZE THE COMPRESSOR TO MEET YOUR SPECIFIC REQUIREMENTS WITHOUT PAYING FOR ITEMS YOU DO NOT NEED.

Filtration for instrument quality air.

Aftercooler.

Special paint.

Hose reels, single and dual.

Spark arrestor.

Cold weather starting aid.

Fuel level gauge.

Brakes (Recommended where required by law.)

Mechanical parking brakes.

Ball hitch.

Retractable pneumatic swivel third wheel.

Air filter maintenance indicators.

Gauge package.

Tachometer.

Low fuel shutdown.



SPECIFICATIONS, WEIGHTS AND DIMENSIONS—SULLAIR 375 PORTABLE COMPRESSOR

Delivery @ Rated Pressure	Rated Pressure psig	Pressure Range psig	Designated Model	Weight* (wet) lbs	Weight* (dry) lbs	Length (drawbar) in	Length (canopy) in	Width in	Height in	Track Width in	Tire Size (load range)
375 cfm 177 L/S 10.6 m ³ /min	100 7	80–125 5.5–8.5	2-Wheel	4150 1888	3825 1735	151 3835	95.7 2431	78.9 2004	68.5 1740	67.5 1715	H78 X 15 ST (D)
			Less Running Gear	4020 1823	3705 1681	– –	95.7 2431	58.2 1478	57.5 1460	– –	– –

Engine Make	Engine Type	Engine Model	Displacement cu in	Cylinders	Bore and Stroke in	Rated Speed rpm	Rated Power hp
John Deere (Tier 2 Emission Compliant)	Diesel	4045TF275	275 4507	4	4.19 X 5.00 106 X 127	2250	113 84
Caterpillar (Tier 2 Emission Compliant)	Diesel	3054C	243 4000	4	3.94 X 5.00 100 X 127	2250	108 80

*Weights are for John Deere diesel. For Caterpillar add 90 lbs. (41 kg).



www.sullair.com

SULLAIR CORPORATION, 3700 East Michigan Blvd., Michigan City, IN 46360 Telephone: 1-800-SULLAIR or 1-219-879-5451 Fax: 1-219-874-1504

SULLAIR EUROPE S.A., Zone des Granges, BP 82, 42602 Montbrison, Cedex, France, Telephone: (33) 4.77.96.84.70 Fax: (33) 4.77.96.84.99

SULLAIR ASIA LTD., 74 Joo Koon Circle, Jurong, Singapore 629093, Telephone: (65) 861-1211 Fax: (65) 861-2967 Telex RS25117

SHENZHEN SULLAIR ASIA INTERNATIONAL CO., LTD., Zuo Pao Tai Road, Chiwan, Shekou, Shenzhen 518068, China, Telephone: (86) 755-6851686 Fax: (86) 755-6853473

SULLAIR TAIWAN LTD., 2nd Fl. No. 96, Chien Kuo N. Road, Taipei 104, Taiwan, Telephone: 886-2-505-7256, Fax: 886-2-505-5480

SULLAIR ARGENTINA, Goncalves Dias 1145, 1276 Buenos Aires, Argentina, Telephone: 541-303-0621, Fax: 541-303-0626