

Rigger Special 80-100

Width Across Counterweight:	95.5"
Tread Width, Drive Axle:	74"
Fork Spread (Standard):	98"
Width Over Tires:	101.5"
Outside Turn Radius (Tail Swing):	196"
Inside Turn Radius:	23.25"
Height to Top of "A" Frame:	102"
Height to Top of Counter Weight:	VARIABLES"
Height to Top of Carriage:	99"
Steer Axle CL to Rear of Counterweight:	37"
Wheelbase:	127" to 167"
Underclearance (Mast):	4"
Drive Axle CL to Carriage Face:	37.5"
Overall Length, Less Forks:	199"
Hyd. Counterweight and Stand:	
Truck Length Less Forks:	199"
Truck with Hyd. C.W. Ext.:	235"
Hydraulic counterweight takes truck from 80,000 lb at 24" load center to 100,000 lb at 24" load center	



February 1, 2016

Able Equipment

Load Chart for 80/100

Serial# BM110408

Truck with no weight capacity 25,000 @ 24"

Truck with set in back 4300 Lb 30,000 @ 24

Truck with sliding cwt 20,470 Lb 60,000 @ 24

Truck with sliding cwt 20,470 Lb out 36" 80,000 @ 24

Truck with sliding cwt 20,470 Lb / Top 5275 Lb in
65,000 24" out is 85,000 Lb 24"

Truck with sliding cwt 20,470 plus two top cwts 10,500 in.
80,000 Lb out 36" 100,000 @ 24 load center

Working on books.

Thanks,

Vic Moody
Bristol Manufacturing, Inc.
President