

H190HD₂ - H210HD₂ SPECIFICATIONS

GENERAL	HYSTER		HYSTER		
	H190HD ₂		H210HD ₂		
1	Manufacturer	HYSTER		HYSTER	
2	Model designation	H190HD ₂		H210HD ₂	
3	Power: battery, diesel, LPG, electric mains	Diesel		Diesel	
4	Transmission	SOH TE-10	ZF WG161	SOH TE-10	ZF WG161
5	Brake	Air / Drum	Wet Disc	Air / Drum	Wet Disc
6	Operation: manual, pedestrian, stand, sit, seat	Seat		Seat	
7	Load capacity	19000 (8000)		21000 (9000)	
8	Load center	24 (600)		24 (600)	
9	Unladen weight including front end	27318 (12389)		28012 (12389)	
10	Axle loading with load, front/rear	40127 (18198)	4831 (2191)	43333 (19652)	4525 (2052)
11	Axle loading without load, front/rear	13814 (6265)	13503 (6124)	13733 (6228)	14280 (6476)
12	Tires	Pneumatic		Pneumatic	
13	Tire size, front	10.00-20 14PR		10.00-20 14PR	
14	Tire size, rear	10.00-20 14PR		10.00-20 14PR	
15	Number of wheels, front/rear (X = driven)	4X / 2		4X / 2	
16	Tread width, front	86.2 (2190)		86.2 (2190)	
17	Tread width, rear	76.0 (1930)		76.0 (1930)	
18	Mast tilt, a = forward / b = back	15/12		15/12	
19	Height of mast, lowered	165.0 (4179)		165.0 (4179)	
20	Lift height	212.0 (5401)		212.0 (5401)	
21	Height of mast, extended; without LBE	270.0 (6846)		270.0 (6846)	
22	Overhead guard height (including wiper)	118.7 (3015)		118.7 (3015)	
23	Length to face of forks w/std. carriage	169.0 (4292)		169.0 (4292)	
24	Load distance	28.5 (725)		28.5 (725)	
25	Wheelbase	106.3 (2700)		106.3 (2700)	
26	Overall width - dry brake axle/wet brake axle*	97.80 (2484)		97.80 (2484)	
27	Fork dimensions	2.5/8/48.0 (65/200/1220)		2.5/8/48.0 (65/200/1220)	
28	Fork carriage type	2.56 (65) pin type		2.56 (65) pin type	
29	Fork carriage width (without load backrest)	92.5 (2350)		92.5 (2350)	
30	Out to out dimension, fork positioner*	20.5 - 87.8 (520 - 2230)		20.5 - 87.8 (550-2230)	
31	Sideshift from center of truck*	5.9 (150)		5.9 (150)	
32	Ground clearance under mast, with load	9.8 (248)		9.8 (248)	
33	Ground clearance, center of wheelbase	10.8 (274)		10.8 (274)	
34	Aisle width with pallets 1000 x 1200 wide	225.9 (5739)		225.9 (5739)	
35	Outer turning radius	154.1 (3914)		154.1 (3914)	
	Inner turning radius	8.7 (220)		8.7 (220)	
36	Transmission manufacturer/type	SOH TE-10	ZF WG161	SOH TE-10	ZF WG161
37	Travel speed with load	16.4 (26.4)	19.0 (30.5)	16.4 (26.4)	18.8 (30.2)
	Travel speed without load	17.5 (28.1)	19.4 (31.2)	17.5 (28.1)	19.4 (31.2)
38	Lifting speed loaded (Std. Performance)	90.6 (.46)	90.6 (.46)	90.6 (.46)	90.6 (.46)
	Lifting speed unloaded (Std. Performance)	102.4 (.52)	102.4 (.52)	102.4 (.52)	102.4 (.52)
39	Lowering speed loaded (Std. Performance)	98.4 (.50)	98.4 (.50)	98.4 (.50)	98.4 (.50)
	Lowering speed unloaded (Std. Performance)	95.0 (.48)	95.0 (.48)	95.0 (.48)	95.0 (.48)
40	Lifting speed loaded (High Performance)*	N/A	108.3 (.55)	N/A	108.3 (.55)
	Lifting speed unloaded (High Performance)*	N/A	124.0 (.63)	N/A	124.0 (.63)
41	Lowering speed loaded (High Performance)*	N/A	98.4 (.50)	N/A	98.4 (.50)
	Lowering speed unloaded (High Performance)*	N/A	94.5 (.48)	N/A	94.5 (.48)
42	Tilt speed	5.0		5.0	
43	Drawbar pull with load (at 1 mph/1.6km/h)	196907 (89300)	211901 (96100)	190292 (86300)	211239 (95800)
	Drawbar pull without load (at 1 mph/1.6km/h)	79380 (36000)	79380 (36000)	80483 (36500)	80483 (36500)
44	Maximum drawbar pull with load	230643 (104600)	257544 (116800)	230202 (104400)	257544 (116800)
	Maximum drawbar pull without load	79380 (36000)	79380 (36000)	80483 (36500)	80483 (36500)
45	Gradeability with load (at 1 mph/1.6km/h)	51		47	
	Gradeability without load (at 1 mph/1.6km/h)	32		31	
	Gradeability with load	63		57	
	Gradeability without load	32		31	
46	Service brake air brakes / wet brakes	air		wet	
47	Engine manufacturer/type	Cummins QSB6.7		Cummins QSB6.7	
48	Engine output, in accordance with ISO 14396	155 (116)		155 (116)	
49	Engine torque	440/1500 (597/1500)		440/1500 (597/1500)	
50	Governed speed	2300		2300	
51	Number of cylinders/displacement	6/409 (6/6700)		6/409 (6/6700)	
52	Transmission	3-speed autoshift		3-speed autoshift	
53	Working pressure for attachments	2800 (193)		2800 (193)	
54	Oil flow for attachments	26.4 (100)		26.4 (100)	

CERTIFICATION: These Hyster® lift trucks meet design specifications of Part II ANSI B56.1-1969, as required by OSHA Section 1910.178(a)(2) and also comply with Part III ANSI B56.1-revision in effect at time of manufacture. Certification of compliance with the applicable ANSI standards appears on the lift truck. Performance specifications are for a truck equipped as described under Standard Equipment on this Technical Guide. Performance specifications are affected by the condition of the vehicle and how it is equipped, as well as by the nature, condition of the operating area, proper service and maintenance of the vehicle. If these specifications are critical, the proposed application should be discussed with your dealer.

H230HD₂ - H230HD₂S SPECIFICATIONS

GENERAL	HYSTER		HYSTER	
	H230HD ₂		H230HD ₂ S	
1	Manufacturer		HYSTER	
2	Model designation		H230HD ₂	
3	Power: battery, diesel, LPG, electric mains		Diesel	
4	Transmission		SOH TE-10	ZF WG161
5	Brake		Air / Drum	Wet Disc
6	Operation: manual, pedestrian, stand, sit, seat		Seat	
7	Load capacity	lbs (kg)	23000 (10000)	
8	Load center	in (mm)	24 (600)	
9	Unladen weight including front end	lbs (kg)	32169 (14589)	
10	Axle loading with load, front/rear	lbs (kg)	48347 (21926) 5872 (2663)	48347 (21926) 5872 (2663)
11	Axle loading without load, front/rear	lbs (kg)	15940 (7229) 16229 (7360)	15940 (7229) 16229 (7360)
12	Tires		Pneumatic	Pneumatic
13	Tire size, front		10.00-20 14PR	10.00-20 14PR
14	Tire size, rear		10.00-20 14PR	10.00-20 14PR
15	Number of wheels, front/rear (X = driven)		4X / 2	4X / 2
16	Tread width, front	in (mm)	86.2 (2190)	86.2 (2190)
17	Tread width, rear	in (mm)	76.0 (1930)	76.0 (1930)
18	Mast tilt, a = forward / b = back	degrees	15/12	15/12
19	Height of mast, lowered	in (mm)	176.0 (4453)	176.0 (4453)
20	Lift height	in (mm)	213.0 (5411)	213.0 (5411)
21	Height of mast, extended; without LBE	in (mm)	281.0 (7118)	281.0 (7118)
22	Overhead guard height (including wiper)	in (mm)	119.4 (3033)	119.4 (3033)
23	Length to face of forks w/std. carriage	in (mm)	177.0 (4495)	177.0 (4495)
24	Overall width - dry brake axle/wet brake axle*	in (mm)	97.80 (2484)	96.30 (2446)
25	Load distance	in (mm)	29.9 (760)	
26	Wheelbase	in (mm)	114.2 (2900)	
27	Fork dimensions	in (mm)	3.0/8/48.0 (75/200/1220)	
28	Fork carriage type	in (mm)	2.95 (75) pin type	
29	Fork carriage width (without load backrest)	in (mm)	92.5 (2350)	
30	Out to out dimension, fork positioner*	in (mm)	20.5 - 87.8 (520 - 2230)	
31	Sideshift from center of truck*	in (mm)	5.9 (150)	
32	Ground clearance under mast, with load	in (mm)	8.9 (225)	
33	Ground clearance, center of wheelbase	in (mm)	11.5 (292)	
34	Aisle width with pallets 1000 x 1200 wide	in (mm)	235.1 (5971)	
35	Outer turning radius	in (mm)	161.9 (4111)	
	Inner turning radius	in (mm)	9.9 (252)	
36	Transmission manufacturer/type		SOH TE-10	ZF WG161
37	Travel speed with load	mph (kph)	15.5 (25.0)	19.0 (30.6)
	Travel speed without load	mph (kph)	18.5 (29.7)	19.9 (32.0)
38	Lifting speed loaded (Std. Performance)	fpm (m/sec)	68.9 (.35)	68.9 (.35)
	Lifting speed unloaded (Std. Performance)	fpm (m/sec)	78.7 (.40)	78.7 (.40)
39	Lowering speed loaded (Std. Performance)	fpm (m/sec)	96.5 (.49)	96.5 (.49)
	Lowering speed unloaded (Std. Performance)	fpm (m/sec)	91.0 (.46)	91.0 (.46)
40	Lifting speed loaded (High Performance)*	fpm (m/sec)	N/A	82.7 (.42)
	Lifting speed unloaded (High Performance)*	fpm (m/sec)	N/A	94.5 (.48)
41	Lowering speed loaded (High Performance)*	fpm (m/sec)	N/A	98.4 (.50)
	Lowering speed unloaded (High Performance)*	fpm (m/sec)	N/A	90.6 (.46)
42	Tilt speed	deg/sec	5.0	
43	Drawbar pull with load (at 1 mph/1.6km/h)	lbs (kg)	189189 (85800)	67473 (30600)
	Drawbar pull without load (at 1 mph/1.6km/h)	lbs (kg)	90846 (41200)	90846 (41200)
44	Maximum drawbar pull with load	lbs (kg)	220059 (99800)	243432 (110400)
	Maximum drawbar pull without load	lbs (kg)	90846 (41200)	90846 (41200)
45	Gradeability with load (at 1 mph/1.6km/h)	%	38	
	Gradeability without load (at 1 mph/1.6km/h)	%	31	
	Gradeability with load	%	46	
	Gradeability without load	%	31	
46	Service brake air brakes / wet brakes		air	wet
47	Engine manufacturer/type		Cummins QSB6.7	Cummins QSB6.7
48	Engine output, in accordance with ISO 14396	hp (kW)	155 (116)	
49	Engine torque	lb-ft/rpm (Nm/rpm)	440/1500 (597/1500)	
50	Governed speed	rpm	2300	
51	Number of cylinders/displacement	in ³ (cm ³)	6/409 (6/6700)	
52	Transmission		3-speed autoshift	
53	Working pressure for attachments	psi (bar)	2800 (193)	
54	Oil flow for attachments	gpm (l/min)	26.4 (100)	

CERTIFICATION: These Hyster® lift trucks meet design specifications of Part II ANSI B56.1-1969, as required by OSHA Section 1910.178(a)(2) and also comply with Part III ANSI B56.1-revision in effect at time of manufacture. Certification of compliance with the applicable ANSI standards appears on the lift truck. Performance specifications are for a truck equipped as described under Standard Equipment on this Technical Guide. Performance specifications are affected by the condition of the vehicle and how it is equipped, as well as by the nature, condition of the operating area, proper service and maintenance of the vehicle. If these specifications are critical, the proposed application should be discussed with your dealer.

H250HD₂ - H280HD₂ SPECIFICATIONS

GENERAL	WT.	H250HD ₂				H280HD ₂			
		H250HD ₂		H280HD ₂		H250HD ₂		H280HD ₂	
1	Manufacturer	HYSTER				HYSTER			
2	Model designation	H250HD ₂				H280HD ₂			
3	Power: battery, diesel, LPG, electric mains	Diesel				Diesel			
4	Transmission	SOH TE-10		ZF WG161		SOH TE-10		ZF WG161	
5	Brake	Air / Drum		Wet Disc		Air / Drum		Wet Disc	
6	Operation: manual, pedestrian, stand, sit, seat	Seat				Seat			
7	Load capacity	25000 (12000)				28000 (12000)			
8	Load center	24 (600)				24 (600)			
9	Unladen weight including front end	32581 (15444)				34054 (15444)			
10	Axle loading with load, front/rear	52772 (24773) 4810 (2672)		52772 (24773) 4810 (2672)		54624 (24770) 5892 (2672)		54624 (24770) 5892 (2672)	
11	Axle loading without load, front/rear	15938 (7136) 16643 (8308)		15938 (7136) 16643 (8308)		15735 (7136) 18319 (8308)		15735 (7136) 18319 (8308)	
12	Tires	Pneumatic				Pneumatic			
13	Tire size, front	10.00-20 14PR		10.00-20 14PR		10.00-20 14PR		10.00-20 14PR	
14	Tire size, rear	10.00-20 14PR		10.00-20 14PR		10.00-20 14PR		10.00-20 14PR	
15	Number of wheels, front/rear (X = driven)	4X/2		4X/2		4X / 2		4X / 2	
16	Tread width, front	86.2 (2190)		86.2 (2190)		86.2 (2190)		86.2 (2190)	
17	Tread width, rear	76.0 (1930)		76.0 (1930)		76.0 (1930)		76.0 (1930)	
18	Mast tilt, a = forward / b = back	15/12		15/12		15/12		15/12	
19	Height of mast, lowered	176.0 (4453)		176.0 (4453)		176.0 (4453)		176.0 (4453)	
20	Lift height	213.0 (5411)		213.0 (5411)		213.0 (5411)		213.0 (5411)	
21	Height of mast, extended; without LBE	281.0 (7118)		281.0 (7118)		281.0 (7118)		281.0 (7118)	
22	Overhead guard height (including wiper)	119.4 (3033)		119.4 (3033)		119.4 (3033)		119.4 (3033)	
23	Length to face of forks w/std. carriage	177.0 (4495)		177.0 (4495)		177.0 (4495)		177.0 (4495)	
24	Overall width - dry brake axle/wet brake axle*	97.80 (2484)		96.30 (2446)		97.8 (2484)		96.30 (2446)	
25	Load distance	29.9 (760)				29.9 (760)			
26	Wheelbase	114.2 (2900)				114.2 (2900)			
27	Fork dimensions	3.0/8/48.0 (75/200/1220)		3.0/8/48.0 (75/200/1220)		3.0/8/48.0 (75/200/1220)		3.0/8/48.0 (75/200/1220)	
28	Fork carriage type	2.95 (75) pin type		2.95 (75) pin type		2.95 (75) pin type		2.95 (75) pin type	
29	Fork carriage width (without load backrest)	92.5 (2350)		92.5 (2350)		92.5 (2350)		92.5 (2350)	
30	Out to out dimension, fork positioner*	20.5 - 87.8 (520-2230)		20.5 - 87.8 (520-2230)		20.5 - 87.8 (520-2230)		20.5 - 87.8 (520-2230)	
31	Sideshift from center of truck*	5.9 (150)		5.9 (150)		5.9 (150)		5.9 (150)	
32	Ground clearance under mast, with load	8.9 (225)		8.9 (225)		8.9 (225)		8.9 (225)	
33	Ground clearance, center of wheelbase	11.5 (292)		11.5 (292)		11.5 (292)		11.5 (292)	
34	Aisle width with pallets 1000 x 1200 wide	235.1 (5971)		235.1 (5971)		235.1 (5971)		235.1 (5971)	
35	Outer turning radius	161.9 (4111)		161.9 (4111)		161.9 (4111)		161.9 (4111)	
	Inner turning radius	9.9 (252)		9.9 (252)		9.9 (252)		9.9 (252)	
36	Transmission manufacturer/type	SOH TE-10		ZF WG161		SOH TE-10		ZF WG161	
37	Travel speed with load	15.5 (25.0)		18.8 (30.3)		15.5 (25.0)		18.8 (30.3)	
	Travel speed without load	18.5 (29.7)		19.9 (32.0)		18.5 (29.7)		19.9 (32.0)	
38	Lifting speed loaded (Std. Performance)	68.9 (.35)		68.9 (.35)		68.9 (.35)		68.9 (.35)	
	Lifting speed unloaded (Std. Performance)	78.7 (.40)		78.7 (.40)		78.7 (.40)		78.7 (.40)	
39	Lowering speed loaded (Std. Performance)	96.5 (.49)		96.5 (.49)		96.5 (.49)		96.5 (.49)	
	Lowering speed unloaded (Std. Performance)	91.0 (.46)		91.0 (.46)		91.0 (.46)		91.0 (.46)	
40	Lifting speed loaded (High Performance)*	N/A		82.7 (.42)		N/A		82.7 (.42)	
	Lifting speed unloaded (High Performance)*	N/A		94.5 (.48)		N/A		94.5 (.48)	
41	Lowering speed loaded (High Performance)*	N/A		98.4 (.50)		N/A		98.4 (.50)	
	Lowering speed unloaded (High Performance)*	N/A		90.6 (.46)		N/A		90.6 (.46)	
42	Tilt speed	5.0		5.0		5.0		5.0	
43	Drawbar pull with load (at 1 mph/1.6km/h)	187866 (85200)		198450 (90000)		187866 (85200)		198450 (90000)	
	Drawbar pull without load (at 1 mph/1.6km/h)	99005 (44900)		99005 (44900)		99005 (44900)		99005 (44900)	
44	Maximum drawbar pull with load	218736 (99200)		243432 (110400)		218736 (99200)		243432 (110400)	
	Maximum drawbar pull without load	99005 (44900)		99005 (44900)		99005 (44900)		99005 (44900)	
45	Gradeability with load (at 1 mph/1.6km/h)	32		34		32		34	
	Gradeability without load (at 1 mph/1.6km/h)	30		30		30		30	
	Gradeability with load	38		46		38		46	
	Gradeability without load	30		30		30		30	
46	Service brake air brakes / wet brakes	air		wet		air		wet	
47	Engine manufacturer/type	Cummins QSB6.7		Cummins QSB6.7		Cummins QSB6.7		Cummins QSB6.7	
48	Engine output, in accordance with ISO 14396	155 (116)		155 (116)		155 (116)		155 (116)	
49	Engine torque	440/1500 (597/1500)		440/1500 (597/1500)		440/1500 (597/1500)		440/1500 (597/1500)	
50	Governed speed	2300		2300		2300		2300	
51	Number of cylinders/displacement	6/409 (6/6700)		6/409 (6/6700)		6/409 (6/6700)		6/409 (6/6700)	
52	Transmission	3-speed autoshift				3-speed autoshift			
53	Working pressure for attachments	2800 (193)		2801 (193)		2800 (193)		2801 (193)	
54	Oil flow for attachments	26.4 (100)		26.4 (100)		26.4 (100)		26.4 (100)	

CERTIFICATION: These Hyster® lift trucks meet design specifications of Part II ANSI B56.1-1969, as required by OSHA Section 1910.178(a)(2) and also comply with Part III ANSI B56.1-revision in effect at time of manufacture. Certification of compliance with the applicable ANSI standards appears on the lift truck. Performance specifications are for a truck equipped as described under Standard Equipment on this Technical Guide. Performance specifications are affected by the condition of the vehicle and how it is equipped, as well as by the nature, condition of the operating area, proper service and maintenance of the vehicle. If these specifications are critical, the proposed application should be discussed with your dealer.

H300HD₂ - H330HD₂ SPECIFICATIONS

GENERAL	HYSTER		HYSTER	
	H300HD ₂		H330HD ₂	
1	Manufacturer			
2	Model designation			
3	Power: battery, diesel, LPG, electric mains			
4	SOH TE-10		ZF WG161	
5	Air / Drum		Wet Disc	
6	Operation: manual, pedestrian, stand, sit, seat			
7	Seat		Seat	
8	30000 (13000)		33000 (14000)	
9	24 (600)		24 (600)	
10	Unladen weight including front end			
11	39825 (18061)		41436 (18792)	
12	63352 (28731) 5138 (2330)		63352 (28731) 5138 (2330)	
13	21988 (9972) 17836 (8089)		21988 (9972) 17836 (8089)	
14	66646 (30225) 5660 (2567)		66646 (30225) 5660 (2567)	
15	22101 (10023) 19336 (8769)		22101 (10023) 19336 (8769)	
16	Tires			
17	Pneumatic			
18	12.00-20 16PR			
19	12.00-20 16PR			
20	4X / 2			
21	4X / 2			
22	89.6 (2276)			
23	89.6 (2276)			
24	78.7 (2000)			
25	78.7 (2000)			
26	15/12			
27	15/12			
28	176.0 (4466)			
29	176.0 (4466)			
30	212.0 (5400)			
31	212.0 (5400)			
32	281.0 (7120)			
33	281.0 (7120)			
34	119.8 (3043)			
35	119.8 (3043)			
36	120.6 (3064)			
37	120.6 (3064)			
38	197.0 (5004)			
39	197.0 (5004)			
40	33.9 (862)			
41	33.9 (862)			
42	129.9 (3300)			
43	129.9 (3300)			
44	102.64 (2607)			
45	102.64 (2607)			
46	102.64 (2607)			
47	102.64 (2607)			
48	3.5/8/60 (90/200/1525)			
49	3.5/8/60 (90/200/1525)			
50	3.5/8/60 (90/200/1525)			
51	3.5/8/60 (90/200/1525)			
52	3.35 (85) pin type			
53	3.35 (85) pin type			
54	3.35 (85) pin type			
55	3.35 (85) pin type			
56	98.4 (2500)			
57	98.4 (2500)			
58	98.4 (2500)			
59	98.4 (2500)			
60	20.5 - 93.7 (520-2380)			
61	20.5 - 93.7 (520-2380)			
62	20.5 - 93.7 (520-2380)			
63	20.5 - 93.7 (520-2380)			
64	5.9 (150)			
65	5.9 (150)			
66	5.9 (150)			
67	5.9 (150)			
68	6.2 (157)			
69	6.2 (157)			
70	6.2 (157)			
71	6.2 (157)			
72	12.8 (325)			
73	12.8 (325)			
74	12.8 (325)			
75	12.8 (325)			
76	257.7 (6546)			
77	257.7 (6546)			
78	257.7 (6546)			
79	257.7 (6546)			
80	180.5 (4584)			
81	180.5 (4584)			
82	180.5 (4584)			
83	180.5 (4584)			
84	18.1 (459)			
85	18.1 (459)			
86	18.1 (459)			
87	18.1 (459)			
88	SOH TE-10			
89	ZF WG161			
90	SOH TE-10			
91	ZF WG161			
92	15.2 (24.5)			
93	15.2 (24.5)			
94	15.2 (24.5)			
95	15.2 (24.5)			
96	17.2 (27.6)			
97	17.2 (27.6)			
98	17.2 (27.6)			
99	17.2 (27.6)			
100	55.1 (.28)			
101	55.1 (.28)			
102	55.1 (.28)			
103	55.1 (.28)			
104	84.0 (.42)			
105	84.0 (.42)			
106	84.0 (.42)			
107	84.0 (.42)			
108	94.5 (.48)			
109	94.5 (.48)			
110	94.5 (.48)			
111	94.5 (.48)			
112	87.0 (.44)			
113	87.0 (.44)			
114	87.0 (.44)			
115	87.0 (.44)			
116	N/A			
117	N/A			
118	N/A			
119	N/A			
120	N/A			
121	N/A			
122	N/A			
123	N/A			
124	N/A			
125	N/A			
126	N/A			
127	N/A			
128	N/A			
129	N/A			
130	N/A			
131	N/A			
132	N/A			
133	N/A			
134	N/A			
135	N/A			
136	N/A			
137	N/A			
138	N/A			
139	N/A			
140	N/A			
141	N/A			
142	N/A			
143	N/A			
144	N/A			
145	N/A			
146	N/A			
147	N/A			
148	N/A			
149	N/A			
150	N/A			
151	N/A			
152	N/A			
153	N/A			
154	N/A			
155	N/A			
156	N/A			
157	N/A			
158	N/A			
159	N/A			
160	N/A			
161	N/A			
162	N/A			
163	N/A			
164	N/A			
165	N/A			
166	N/A			
167	N/A			
168	N/A			
169	N/A			
170	N/A			
171	N/A			
172	N/A			
173	N/A			
174	N/A			
175	N/A			
176	N/A			
177	N/A			
178	N/A			
179	N/A			
180	N/A			
181	N/A			
182	N/A			
183	N/A			
184	N/A			
185	N/A			
186	N/A			
187	N/A			
188	N/A			
189	N/A			
190	N/A			
191	N/A			
192	N/A			
193	N/A			
194	N/A			
195	N/A			
196	N/A			
197	N/A			
198	N/A			
199	N/A			
200	N/A			
201	N/A			
202	N/A			
203	N/A			
204	N/A			
205	N/A			
206	N/A			
207	N/A			
208	N/A			
209	N/A			
210	N/A			
211	N/A			
212	N/A			
213	N/A			
214	N/A			
215	N/A			
216	N/A			
217	N/A			
218	N/A			
219	N/A			
220	N/A			
221	N/A			
222	N/A			
223	N/A			
224	N/A			
225	N/A			
226	N/A			
227	N/A			
228	N/A			
229	N/A			
230	N/A			
231	N/A			
232	N/A			
233	N/A			
234	N/A			
235	N/A			
236	N/A			
237	N/A			
238	N/A			
239	N/A			
240	N/A			
241	N/A			
242	N/A			
243	N/A			
244	N/A			
245	N/A			
246	N/A			
247	N/A			
248	N/A			
249	N/A			
250	N/A			
251	N/A			
252	N/A			
253	N/A			
254	N/A			
255	N/A			
256	N/A			
257	N/A			
258	N/A			
259	N/A			
260	N/A			
261	N/A			
262	N/A			
263	N/A			
264	N/A			
265	N/A			
266	N/A			
267	N/A			
268	N/A			
269	N/A			
270	N/A			
271	N/A			
272	N/A			
273	N/A			
274	N/A			
275	N/A			
276	N/A			
277	N/A			
278	N/A			
279	N/A			
280	N/A			
281	N/A			
282	N/A			
283	N/A			
284	N/A			
285	N/A			
286	N/A			
287	N/A			
288	N/A			
289	N/A			
290	N/A			
291	N/A			
292	N/A			
293	N/A			
294	N/A			
295	N/A			
296	N/A			
297	N/A			
298	N/A			
299	N/A			
300	N/A			
301	N/A			
302	N/A			
303	N/A			
304	N/A			
305	N/A			
306	N/A			
307	N/A			
308	N/A			
309	N/A			
310	N/A			
311	N/A			
312	N/A			
313	N/A			
314	N/A			
315	N/A			
316	N/A			
317	N/A			
318	N/A			
319	N/A			
320	N/A			
321	N/A			
322	N/A			
323	N/A			
324	N/A			
325	N/A			
326	N/A			
327	N/A			
328	N/A			
329	N/A			
330	N/A			
331	N/A			
332	N/A			
333	N/A			
334	N/A			
335	N/A			
336	N/A			
337	N/A			
338	N/A			
339	N/A			
340	N/A			
341	N/A			
342	N/A			
343	N/A			
344	N/A			
345	N/A			
346	N/A			
347	N/A			
348	N/A			
349	N/A			
350	N/A			
351	N/A			
352	N/A			
353	N/A			
354	N/A			
355	N/A			
356	N/A			
357	N/A			
358	N/A			
359	N/A			
360	N/A			
361	N/A			
362	N/A			
363	N/A			
364	N/A			
365	N/A			
366	N/A			
367	N/A			
368	N/A			
369	N/A			
370	N/A			
371	N/A			
372	N/A			
373	N/A			
374	N/A			
375	N/A			
376	N/A			
377	N/A			
378	N/A			
379	N/A			
380	N/A			
381	N/A			
382	N/A			
383	N/A			
384	N/A			
385	N/A			
386	N/A			
387	N/A			
388	N/A			
389	N/A			
390	N/A			
391	N/A			
392	N/A			
393	N/A			
394	N/A			
395	N/A			
396	N/A			
397	N/A			
398	N/A			
399	N/A			
400	N/A			
401	N/A			
402	N/A			
403	N/A			
404	N/A			
405	N/A			
406	N/A			
407	N/A			
408	N/A			
409	N/A			
410	N/A			
411	N/A			
412	N/A			
413	N/A			
414	N/A			
415	N/A			
416				

H360HD₂ SPECIFICATIONS

GENERAL	1	Manufacturer	HYSTER			
	2	Model designation	H360HD ₂			
	3	Power: battery, diesel, LPG, electric mains	Diesel			
	4	Transmission	SOH TE-10		ZF WG161	
	5	Brake	Air / Drum		Wet Disc	
	6	Operation: manual, pedestrian, stand, sit, seat	Seat			
WT.	7	Load capacity	lbs (kg) 36000 (16000)			
	8	Load center	in (mm) 24 (600)			
	9	Unladen weight including front end	lbs (kg) 43763 (19847)			
WHEELS	10	Axle loading with load, front/rear	72966 (33091) 6077 (2756)		72966 (33091) 6077 (2756)	
	11	Axle loading without load, front/rear	22054 (10002) 21708 (9845)		22054 (10002) 21708 (9845)	
	12	Tires	Pneumatic		Pneumatic	
	13	Tire size, front	12.00-20 16PR		12.00-20 16PR	
	14	Tire size, rear	12.00-20 16PR		12.00-20 16PR	
	15	Number of wheels, front/rear (X = driven)	4X / 2		4X / 2	
	16	Tread width, front	in (mm) 89.6 (2276)		89.6 (2276)	
	17	Tread width, rear	in (mm) 78.7 (2000)		78.7 (2000)	
	18	Mast tilt, a = forward / b = back	degrees 15/12		15/12	
	19	Height of mast, lowered	in (mm) 176.0 (4466)		176.0 (4466)	
	20	Lift height	in (mm) 212.0 (5400)		212.0 (5400)	
DIMENSIONS	21	Height of mast, extended; without LBE	in (mm) 281.0 (7120)		281.0 (7120)	
	22	Overhead guard height (including wiper)	in (mm) 120.6 (3064)		120.6 (3064)	
	23	Length to face of forks w/std. carriage	in (mm) 197.0 (5004)		197.0 (5004)	
	24	Load distance	in (mm) 33.9 (862)			
	25	Wheelbase	in (mm) 129.9 (3300)			
	26	Overall width - dry brake axle/wet brake axle*	in (mm) 102.64 (2607)		102.64 (2607)	
	27	Fork dimensions	in (mm) 3.5/8/60 (90/200/1525)		3.5/8/60 (90/200/1525)	
	28	Fork carriage type	in (mm) 3.35 (85) pin type		3.35 (85) pin type	
	29	Fork carriage width (without load backrest)	in (mm) 98.4 (2500)		98.4 (2500)	
	30	Out to out dimension, fork positioner*	in (mm) 20.5 - 93.7 (520-2380)		20.5 - 93.7 (520-2380)	
	31	Sideshift from center of truck*	in (mm) 5.9 (150)		5.9 (150)	
	32	Ground clearance under mast, with load	in (mm) 7.0 (178)		7.0 (178)	
	33	Ground clearance, center of wheelbase	in (mm) 13.6 (346)		13.6 (346)	
	34	Aisle width with pallets 1000 x 1200 wide	in (mm) 257.7 (6546)		257.7 (6546)	
	35	Outer turning radius	in (mm) 180.5 (4584)		180.5 (4584)	
	36	Inner turning radius	in (mm) 18.0 (458)		18.0 (458)	
	PERFORMANCE	36	Transmission manufacturer/type	SOH TE-10		ZF WG161
37		Travel speed with load	mph (kph) 14.5 (23.4)		16.3 (26.3)	
		Travel speed without load	mph (kph) 17.0 (27.3)		17.3 (27.9)	
38		Lifting speed loaded (Std. Performance)	fpm (m/sec) 55.1 (.28)		55.1 (.28)	
		Lifting speed unloaded (Std. Performance)	fpm (m/sec) 84.0 (.42)		84.0 (.42)	
39		Lowering speed loaded (Std. Performance)	fpm (m/sec) 94.5 (.48)		94.5 (.48)	
		Lowering speed unloaded (Std. Performance)	fpm (m/sec) 87.0 (.44)		87.0 (.44)	
40		Lifting speed loaded (High Performance)*	fpm (m/sec) 66.9 (.34)		66.9 (.34)	
		Lifting speed unloaded (High Performance)*	fpm (m/sec) 98.4 (.50)		98.4 (.50)	
41		Lowering speed loaded (High Performance)*	fpm (m/sec) 98.4 (.50)		98.4 (.50)	
		Lowering speed unloaded (High Performance)*	fpm (m/sec) 90.6 (.46)		90.6 (.46)	
42		Tilt speed	deg/sec 3.9		3.9	
43		Drawbar pull with load (at 1 mph/1.6km/h)	lbs (kg) 207050 (93900)		224028 (101600)	
		Drawbar pull without load (at 1 mph/1.6km/h)	lbs (kg) 118629 (53800)		118629 (53800)	
44		Maximum drawbar pull with load	lbs (kg) 249165 (113000)		275405 (124900)	
		Maximum drawbar pull without load	lbs (kg) 118629 (53800)		118629 (53800)	
45		Gradeability with load (at 1 mph/1.6km/h)	% 28		30	
	Gradeability without load (at 1 mph/1.6km/h)	% 31		31		
	Gradeability with load	% 35		37		
	Gradeability without load	% 31		31		
46	Service brake air brakes / wet brakes	air		wet		
ENGINE	47	Engine manufacturer/type	Cummins QSB6.7		Cummins QSB6.7	
	48	Engine output, in accordance with ISO 14396	hp (kW) 155 (116)		155 (116)	
	49	Engine torque	lb-ft/rpm (Nm/rpm) 440/1500 (597/1500)		440/1500 (597/1500)	
	50	Governed speed	rpm 2300		2300	
	51	Number of cylinders/displacement	in ³ (cm ³) 6/409 (6/6700)		6/409 (6/6700)	
OTHER	52	Transmission	3-speed autoshift		3-speed autoshift	
	53	Working pressure for attachments	psi (bar) 2800 (193)		2800 (193)	
	54	Oil flow for attachments	gpm (l/min) 26.4 (100)		26.4 (100)	

CERTIFICATION: These Hyster® lift trucks meet design specifications of Part II ANSI B56.1-1969, as required by OSHA Section 1910.178(a)(2) and also comply with Part III ANSI B56.1-revision in effect at time of manufacture. Certification of compliance with the applicable ANSI standards appears on the lift truck. Performance specifications are for a truck equipped as described under Standard Equipment on this Technical Guide. Performance specifications are affected by the condition of the vehicle and how it is equipped, as well as by the nature, condition of the operating area, proper service and maintenance of the vehicle. If these specifications are critical, the proposed application should be discussed with your dealer.

H190HD₂ - H360HD₂ MAST DIMENSIONS

H190-210HD₂ MAST DIMENSIONS in. (mm)

Maximum Fork Height (Top of Forks)	Overall Lowered Height	Overall Extended Height without Load Backrest Ext.	Full Free-Lift	Approx. Total Wgt. of Standard Equipped Truck w/o Load	
				H190HD ₂ lb. (kg)	H210HD ₂ lb. (kg)
2-STAGE NO FREE-LIFT (NO FL) VISTA®					
147 (3751)	133 (3353)	205 (5196)	N/A	26764 (12140)	27459 (12455)
183 (4651)	150 (3803)	240 (6096)	N/A	27267 (12368)	27961 (12683)
212 (5401)	165 (4178)	270 (6846)	N/A	27500 (12474)	28915 (12879)
3-STAGE VISTA®					
220 (5600)	120 (3045)	277 (7073)	56 (1435)	36367 (16496)	37062 (16811)
236 (6000)	126 (3178)	293 (7430)	61 (1568)	37249 (16896)	37944 (17211)
255 (6500)	132 (3345)	313 (7930)	68 (1735)	38352 (17396)	39046 (17711)
275 (7000)	139 (3511)	332 (8430)	74 (1901)	39454 (17896)	40148 (18211)

H230-280HD₂ MAST DIMENSIONS in. (mm)

Maximum Fork Height (Top of Forks)	Overall Lowered Height	Overall Extended Height without Load Backrest Ext.	Full Free-Lift	Approx. Total Wgt. of Standard Equipped Truck w/o Load			
				H230HD ₂ S lb. (kg)	H230HD ₂ lb. (kg)	H250HD ₂ lb. (kg)	H280HD ₂ lb. (kg)
2-STAGE NO FREE-LIFT (NO FL) VISTA®							
148 (3761)	143 (3628)	216 (5468)	N/A	31425 (14254)	31189 (14147)	31575 (14322)	33074 (15002)
183 (4661)	161 (4078)	251 (6368)	N/A	31901 (14470)	31665 (14363)	32051 (14538)	33550 (15218)
213 (5411)	176 (4453)	281 (7118)	N/A	32377 (14686)	32141 (14579)	32527 (14754)	34026 (15434)
244 (6205)	192 (4853)	312 (7918)	N/A	32774 (14866)	32538 (14759)	32924 (14934)	34423 (15614)
3-STAGE VISTA®							
220 (5600)	120 (3045)	277 (7073)	56 (1435)	39494 (17914)	39258 (17807)	39644 (17982)	41143 (18662)
236 (6000)	126 (3178)	293 (7430)	61 (1568)	40375 (18314)	40140 (18207)	40525 (18382)	42025 (19062)
255 (6500)	132 (3345)	313 (7930)	68 (1735)	41478 (18814)	41242 (18707)	41628 (18882)	43127 (19562)
275 (7000)	139 (3511)	332 (8430)	74 (1901)	42580 (19314)	42344 (19207)	42730 (19382)	44229 (20062)

H300-360HD₂ MAST DIMENSIONS in. (mm)

Maximum Fork Height (Top of Forks)	Overall Lowered Height	Overall Extended Height without Load Backrest Ext.	Full Free-Lift	Approx. Total Wgt. of Standard Equipped Truck w/o Load		
				H300HD ₂ lb. (kg)	H330HD ₂ lb. (kg)	H360HD ₂ lb. (kg)
2-STAGE NO FREE-LIFT (NO FL) VISTA®						
147 (3750)	144 (3641)	216 (5470)	N/A	37749 (17123)	39361 (17854)	41687 (18609)
183 (4650)	162 (4091)	251 (6370)	N/A	38382 (17410)	39994 (18141)	42320 (19196)
212 (5400)	176 (4466)	281 (7120)	N/A	39026 (17702)	40368 (18433)	42963 (19488)
244 (6200)	192 (4866)	312 (7920)	N/A	39509 (17921)	41120 (18652)	43446 (19707)
3-STAGE VISTA®						
173 (4400)	121 (3070)	240 (6080)	54 (1390)	39476 (17906)	41087 (18637)	43413 (19692)
196 (5000)	129 (3270)	263 (6680)	62 (1590)	39747 (18029)	41358 (18760)	43684 (19815)
236 (6000)	142 (3600)	303 (7680)	75 (1920)	40201 (18235)	41813 (18966)	44138 (20021)
275 (7000)	156 (3940)	342 (8680)	88 (2250)	41096 (18641)	42708 (19372)	45034 (20427)

H190HD₂ - H360HD₂ SPECIFICATIONS

MODEL	A	B	C	D	E	F	G
	in. (mm)	in. (mm)	in. (mm)	percent	in. (mm)	in. (mm)	in. (mm)
H190HD ₂	116.8 (2967)	119.4 (3033)	72.3 (1837)	70.0%	25.7 (653)	31.8 (809)	46.5 (1181)
H210HD ₂	116.8 (2967)	119.4 (3033)	72.3 (1837)	70.0%	25.7 (653)	31.8 (809)	46.5 (1181)
H230HD ₂	116.8 (2967)	119.4 (3033)	72.3 (1837)	75.0%	25.7 (653)	31.8 (809)	46.5 (1181)
H250HD ₂	116.8 (2967)	119.4 (3033)	72.3 (1837)	75.0%	25.7 (653)	31.8 (809)	46.5 (1181)
H280HD ₂	116.8 (2967)	119.4 (3033)	72.3 (1837)	75.0%	25.7 (653)	31.8 (809)	46.5 (1181)
H300HD ₂	118.0 (2990)	120.6 (3064)	74.7 (1899)	86.9%	26.9 (684)	31.8 (809)	46.5 (1181)
H330HD ₂	118.0 (2990)	120.6 (3064)	74.7 (1899)	86.9%	26.9 (684)	31.8 (809)	46.5 (1181)
H360HD ₂	118.0 (2990)	120.6 (3064)	74.7 (1899)	86.9%	26.9 (684)	31.8 (809)	46.5 (1181)

MODEL	STEP HEIGHT				
	in. (mm)	S1	S2	S3	S4
H190HD ₂		15.51 (394)	27.87 (708)	40.24 (1022)	52.60 (1336)
H210HD ₂		15.51 (394)	27.87 (708)	40.24 (1022)	52.60 (1336)
H230HD ₂		15.51 (394)	27.87 (708)	40.24 (1022)	52.60 (1336)
H250HD ₂		15.51 (394)	27.87 (708)	40.24 (1022)	52.60 (1336)
H280HD ₂		15.51 (394)	27.87 (708)	40.24 (1022)	52.60 (1336)
H300HD ₂		18.07 (420)	30.09 (764)	42.11 (1070)	54.13 (1375)
H330HD ₂		18.07 (420)	30.09 (764)	42.11 (1070)	54.13 (1375)
H360HD ₂		18.07 (420)	30.09 (764)	42.11 (1070)	54.13 (1375)

MODEL	CARRIAGE in. (mm)				
	Standard	FP*	Sideshift	SSFP**	DFSSFP***
H190-210HD ₂ (2-Stage)	28.5 (725)	30.5 (775)	30.9 (785)	30.9 (785)	32.9 (836)
H190-210HD ₂ (3-Stage)	34.8 (885)	34.8 (885)	35.9 (911)	35.9 (911)	N/A
H230-280HD ₂ (2-Stage)	29.9 (760)	31.9 (810)	32.2 (819)	32.2 (819)	33.9 (861)
H230-280HD ₂ (3-Stage)	34.8 (885)	34.8 (885)	35.9 (911)	35.9 (911)	N/A
H300-360HD ₂ (2-Stage)	33.9 (862)	33.9 (862)	35.3 (896)	35.3 (896)	37.4 (949)
H300-360HD ₂ (3-Stage)	36.9 (937)	36.9 (937)	39.8 (1012)	39.8 (1012)	N/A

*FP - Fork Positioner

**SSFP - Sideshift Fork Positioner

***DFSSFP - Dual Function Sideshift Fork Positioner