

# ROUGH TERRAIN SCISSOR LIFTS

	<b>3394RT</b>	<b>4394RT</b>
Platform Height – Elevated	10.05 m	13.10 m
A. Platform Height – Lowered	1.57 m	1.79 m
B. Platform Railing Height	1.10 m	1.10 m
C. Stowed Height (Rails Folded)	1.97 m	2.19 m
D. Platform Size	2.18 m x 3.81 m	2.18 m x 3.81 m
Front Deck Extension	1.22 m	1.22 m
Rear Deck Extension	1.22 m	1.22 m
E. Overall Width	2.39 m	2.39 m
F. Overall Length <sup>1</sup>	3.81 m	3.81 m
G. Wheelbase	2.95 m	2.95 m
Ground Clearance	0.30 m	0.30 m
Platform Capacity	1,020 kg	680 kg
Capacity with Optional Deck Extension	905 kg	565 kg
Capacity on Optional Deck Extension	225 kg	225 kg
Lift/Lower Time	30/30 sec.	40/43 sec.
Maximum Drive Height	10.05 m	13.10 m
Gross Vehicle Weight <sup>2</sup>	5,850 kg	6,900 kg
Drive Speed 2WD	–	–
Drive Speed 4WD	6.4 km/h	6.4 km/h
Gradeability 2WD	–	–
Gradeability 4WD	45%	45%
Turning Radius – Inside	2.71 m	2.71 m
Turning Radius – Outside	5.93 m	5.93 m
Axle Oscillation	0.20 m	0.20 m
Tyres	33/1550 x 16.5 Foam Filled	33/1550 x 16.5 Foam Filled
Diesel Engine	34 kW Deutz F3M1011F	34 kW Deutz F3M1011F
Fuel Tank Capacity	113 L	113 L
Hydraulic Reservoir	151 L	151 L

<sup>1</sup> Overall length with optional leveling jacks is 4.75 m.

<sup>2</sup> Certain options or country standards will increase weight.

*Specifications may change to meet country standards or with the addition of optional equipment.*

