

# RTV

# RTV400Ci/RTV500

# SPECIFICATIONS

## Specifications

| Model                                 |  | RTV400Ci   |                                       | RTV500  |  |
|---------------------------------------|--|--|---------------------------------------|---|--|
| Engine                                | Type   | 1-cylinder, GAS, OHC, Air-cooled, EFI  |                                       | 2-cylinder, GAS, OHC, Water-cooled, EFI               |  |
|                                       | Displacement                                   | cu. in. (cc)   | 24.6 (404)                            | 27.8 (456)  |  |
|                                       | Horsepower                                     | HP (kW)/rpm  | 16.0 (11.9) / 4800                    | 15.8 (11.8) / 3600                                    |  |
| Fuel tank capacity                    | U.S. gals (ℓ)                                  | 5.2 (20)   |                                       |   |  |
| Transmission                          |  | CVT PLUS<br>Continuously Variable Transmission (CVT)<br>with Inertial Clutch |                                       | VHT PLUS<br>Variable Hydro Transmission               |  |
| Max. Traveling speed                  | mph (km/h)                                     | 25 (40)  |                                       |   |  |
| Wheels, drive system                  | 4, 4WD w/2WD selection                         |  |                                       |   |  |
| Differential lock                     | Standard; hand operated with mechanical holder |  |                                       |   |  |
| Gear selection                        | Hi-Lo range forward, neutral, reverse          |  |                                       |   |  |
| Brakes                                | Front / Rear                                   | Dry-disc brakes  |                                       |   |  |
|                                       | Parking brake                                  | Rear wheel, hand lever   |                                       |   |  |
| Steering                              | Rack & Pinion                                  |  |                                       |   |  |
| Suspension                            | Front / Rear                                   | Independent, Mac-Pherson strut-type / Semi-independent, Multi-link           |                                       |   |  |
| Dimensions                            | Length   | in. (mm)   | 105.9 (2690)                          |   |  |
|                                       | Width  | in. (mm)   | 54.7 (1390)                           |   |  |
|                                       | Height, overall                                | in. (mm)   | 72 (1829)                             |   |  |
|                                       | Front tread centers                            | in. (mm)   | 40 (1016)                             |   |  |
|                                       | Rear tread centers                             | in. (mm)   | 41 (1041)                             |   |  |
|                                       | Wheelbase                                      | in. (mm)   | 70.9 (1800)                           |   |  |
|                                       | Ground clearance front/rear axle               | in. (mm)   | 8.1 (205) / 6.9 (175)                 |   |  |
|                                       | Turning diameter                               | ft. (m)  | 22.9 (7)                              |   |  |
| Max. rolling weight (Towing capacity) | lbs. (kg)                                      | 1102 (500)   |                                       |   |  |
| Payload capacity                      | lbs. (kg)                                      | 1058 (480)   |                                       | 949 (430)   |  |
| Weight                                | lbs. (kg)                                      | 1246 (565) with ATV Tires, 1257 (570) with HDWS Tires                        |                                       | 1358 (615) with ATV tires, 1369 (620) with HDWS tires |  |
| Cargo bed                             | Width × Length × Depth                         | in. (mm)   | 40.6 (1032) × 33.7 (856) × 11.4 (290) |   |  |
|                                       | Volume   | cu. ft. (m <sup>3</sup> )  | 9.0 (0.25)                            |   |  |
|                                       | Bed height (unloaded)                          | in. (mm)   | 31.9 (810)                            |   |  |
|                                       | Cargo bed load                                 | lbs. (kg)  | 441 (200)                             |   |  |
| Tires                                 | Front  | 24 × 9-12 ATV, 6PLY  |                                       |   |  |
|                                       |  | 24 × 9-12 HDWS, 6PLY   |                                       |   |  |
|                                       | Rear   | 24 × 11-12 ATV, 6PLY   |                                       |   |  |
|                                       |  | 24 × 11-12 HDWS, 6PLY  |                                       |   |  |
| Body color                            | Orange, Camouflage (Realtree® Hardwoods®)      |  |                                       |   |  |
| Speedometer                           | Opt.   |  |                                       |   |  |
| Front guard                           | Opt.   |  |                                       |   |  |
| Headrest                              | Opt.   |  |                                       |   |  |

\*Realtree® is a registered trademark of Jordan Outdoor Enterprises, Ltd.

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this web site are shown with optional accessories. For off-highway use only.