


RTV-X Series

Specifications

RTV-X1120D



Model			RTV-X1120D	
Body color			Kubota Orange	Realtree AP Camo
Engine			KUBOTA D1105-E4-UV	KUBOTA D1105-E4-UV
Make				
Type			3-cylinders, 4-cycle, diesel, OHV	3-cylinders, 4-cycle, diesel, OHV
Displacement			68.5 (1123) cu.in (cc)	68.5 (1123)
Horsepower			24.8 (18.5) @3000 HP (kW)/rpm	24.8 (18.5) @3000
Cooling system			Liquid	Liquid
Battery			650 CCA	650 CCA
Transmission			Variable hydro transmission (VHT-X)	Variable hydro transmission (VHT-X)
Gear selection			Hi-Lo range forward, neutral, reverse	Hi-Lo range forward, neutral, reverse
Max. traveling speed			0-29 (0-46.4) mph (km/h)	0-29 (0-46.4)
4WD system			Limited-slip differential	Limited-slip differential
Front differential				
Rear differential			Foot operated differential lock	Foot operated differential lock
Steering			Hydrostatic power	Hydrostatic power
Brakes			Wet-disc brakes	Wet-disc brakes
Front / Rear				
Parking brake			Rear wheel, hand operated	Rear wheel, hand operated
Suspension			Independent, Dual A-arms with adjustable spring preload	Independent, Dual A-arms with adjustable spring preload
Front suspension				
Front suspension travel			8 (205) in. (mm)	8 (205)
Rear suspension			Independent with coil over shock	Independent with coil over shock
Rear suspension travel			8 (205) in. (mm)	8 (205)
Headlights			Two 37.5 watt blue-tint halogen, optical axis adjustment	Two 37.6 watt blue-tint halogen, optical axis adjustment
Occupant Protective System (OPS)			2.0 (50.8) steel tube in. (mm)	2.0 (50.8) steel tube
Tubular overhead structure				
Seat belts			3-point	3-point
Certification			SAE J2194 and OSHA 1928 ROPS and ANSI B71.9	SAE J2194 and OSHA 1928 ROPS and ANSI B71.9
Dimensions			122.5 (3110) in. (mm)	122.5 (3110)
Length			63.2 (1605) in. (mm)	63.2 (1605)
Width			79.5 (2020) in. (mm)	79.5 (2020)
Height, overall			48.8 (1240) in. (mm)	48.8 (1240)
Front tread centers			48.8 (1240) in. (mm)	48.8 (1240)
Rear tread centers			80.5 (2045) in. (mm)	80.5 (2045)
Wheelbase			13.1 (4.0) ft. (m)	13.1 (4.0)
Turning radius			2061 (935) lbs. (kg)	2061 (935)
Weight			1300 (590) lbs. (kg)	1300 (590)
Towing capacity			1510 (685) lbs. (kg)	1510 (685)
Payload capacity			10.5 (266) in. (mm)	10.5 (266)
Ground clearance			10.4 (263) in. (mm)	10.4 (263)
Front			11.0 (280) in. (mm)	11.0 (280)
Rear			11.0 (280)	11.0 (280)
Under foot platform			Steel	Steel
Cargo bed			Steel	Steel
Material			57.7 (1465) x 40.5 (1030) x 11.2 (285) in. (mm)	57.7 (1465) x 40.5 (1030) x 11.2 (285)
Width x Length x Depth			15.2 (0.43) cu ft. (m3)	15.2 (0.43)
Volume			34.9 (887) in. (mm)	34.9 (887)
Bed height (unloaded)			1102 (500) lbs. (kg)	1102 (500)
Cargo bed load			Hydro power lift	Hydro power lift
Dump			7.9 (30) U.S. gals (L)	7.9 (30)
Fuel tank capacity			84 dB. (A)	84
Sound rating at operator's ear			25x10-12, 6PLY	25x10-12, 6PLY
Tires			25x10-12, 6PLY	25x10-12, 6PLY
Front and Rear			—	—
ATV			Center, bumper and lens	Center, bumper and lens
HDWS			Std.	Std.
TURF			Std.	Std.
Front guard design			Opt.	Opt.
Alloy wheel (not available with Turf tire)			—	—
Hydraulic bed lift			—	—
Spray-on Bed Liner			—	—

*New SAE J1940

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.