

# SSV Series

# Specifications

## SSV65



Model			SSV65
Type of operator station			Open CAB / Closed CAB
Engine	Model		V2607-CR-TE4
	Emission certification		Tier 4
	Gross HP (SAE J1995)	HP (kW)/rpm	64.0 (47.7) / 2700
	Net HP (SAE J1349)	HP (kW)/rpm	63.0 (47.0) / 2700
	Peak Torque @1500 rpm	lbf-ft (Nm)	166 (225)
	Displacement	cu.in. (cc)	159.7 (2615)
	Cylinders		4
	Bore Stroke	in.(mm)	3.5 (87) × 4.4 (110)
	Aspiration		Turbocharged
Loader performance	Rated operating capacity-50% tipping load		1950 (885)
	Tipping load		3900 (1770)
	Breakout force	Bucket	4839 (2195)
		Lift arm	3858 (1750)
	Lift arm path		Vertical
Power train	Standard tire size		10-16.5-8PR
	Chain size ASA#		80
	Travel speed	Low	6.9 (11.1)
		High	11.1 (17.8)
	Traction force		7339 (3329)
	Ground clearance		7.6 (193)
Hydraulic system	Loader hydraulic flow		18.0 (68.0)
	Loader hydraulic pressure		3271 (230)
	Aux. hydraulic flow	Standard	18.0 (68.0)
		High	28.0 (106.0)
Service refill capacities	Hydraulic tank		4.2 (16.0)
	Fuel tank		25.4 (96.0)
Operating weight (Include operator weight 175 lbs.)		lbs. (kg)	6790 (3080) / 7055 (3200)

Note: The above dimensions are based on the machine with std. tires, skid steer type quick coupler, standard bucket and ROPS/FOPS canopy and cabin. The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective structure (ROPS) and seat belt in almost all applications.