

U

U25S

SPECIFICATIONS

Specifications

Model		U25S		
Type of ROPS / OPG (Top Guard Level I)*		Canopy		
Type of tracks		Rubber		
Engine	Model	Kubota D1105-E3		
	Output (SAE J1995 gross)	HP (kW)/rpm	20.9 (15.6) / 2400	
	Output (SAE J1349 net)	HP (kW)/rpm	19.8 (14.8) / 2400	
	Displacement	cu.in. (cc)	68.5 (1123)	
Dimensions	Overall length	ft.in. (mm)	13'7" (4150)	
	Overall height	ft.in. (mm)	7'11" (2420)	
	Overall width	ft.in. (mm)	4'11" (1500)	
	Min. ground clearance	in. (mm)	11.2" (285)	
Hydraulic system	Pump capacity	GPM. (ℓ /min)	7.6 (28.8) Piston × 2 / 5.1 (19.2) Gear × 1	
	Auxiliary hydraulic flow	GPM. (ℓ /min)	12.7 (48)	
	Max. breakout force	Bucket / Arm	lbs. (kgf)	5765 (2615) / 2745 (1245)
Drive system	Travel speed	mph (km/h)	1.6 (2.5) / 2.9 (4.5)	
	Max. drawbar pull	lbs. (kgf)	6745 (3060)	
	Tumbler distance	ft.in. (mm)	5'1" (1560)	
	Crawler length	ft.in. (mm)	6'7" (2000)	
	Shoe width	in. (mm)	11.8" (300)	
	Ground contact pressure	psi (kgf/cm ²)	3.32 (0.23)	
Swing system	Unit swing speed	rpm	9.8	
	Boom swing angle	Left / Right	degree	75 / 55
Blade	Dimensions	Width	ft.in. (mm)	4'11" (1500)
		Height	in. (mm)	11.8" (300)
	Max. lift above ground	in. (mm)	14" (360)	
	Max. drop below ground	in. (mm)	13" (320)	
Hydraulic oil (reservoir/system)	gal (ℓ)	5.8 (22) / 9.8 (37)		
Fuel reservoir	gal (ℓ)	7.4 (28)		
Operating weight (Including operator's weight 175 lbs.)	lbs.(kgf)	5625 (2550)		

* OPG (Top Guard Level I) in accordance with ISO10262 is equivalent in definition to FOPS (Falling Object Protective Structure).

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt for almost all applications.

DIMENSIONS

